

STA-3/4 Periphyton-Based Stormwater Treatment Area Project Update

Tracey Piccone, P.E.,

Chief Consulting Engineer Water Quality Treatment Technologies Section

Quarterly Long-Term Plan Communications Meeting

May 23, 2012



SOUTH FLORIDA WATER MANAGEMENT DISTRICT



PSTA Project Update

- Structural Modifications to improve flow and load estimates
 - Modified G-390B to improve flow measurements
 - Modified one pump at G-388 pump station to reduce flow rate
 - Modified vegetation strips
 - Seepage estimates and water budget improvements
 - Proposed HW sensor at G-378E and TW sensor at G-379E
- PSTA Project Research Plan





G-390B PSTA Cell Inflow Structure Upstream Side



G-390B Modification Design



sfwmd_gov

G-390B Modification Installation – October 2011







G-388 Outflow Pump Station Modifications



G-388 Outflow Pump Station Modifications

- Pump Speed of Pump #2 changed from 350 rpm to 224 rpm on August 11, 2011
- Revised flow rating equation is now being used to compute flow through Pump #2



Reference: FLOW RATING ANALYSIS FOR PUMP UNIT 2 AT PUMP STATION G388 (Sheng Yue and Emile Damisse, February 2012)

sfwmd.gov

G-388 Outflow Pump Station Modifications



Figure 2. Discharge pipes shown with Pump #2 operating under 222 RPMs.



Figure 3. Making tachometer reading on Pump #2 impeller shaft.



Figure 4. Showing channel cross-section where flow was measured.



Figure 5. Close-up of tachometer display for Pump #2.

sfwmd.gov

Reference: ADCP Streamflow Measurement Report for G-388 Pump Station - August 31, 2011

G-388 Outflow Pump Station Modifications





Plots by Tom James (DBKEYS TZ220 and TZ221)



sfwmd.gov

PSTA Cell Vegetation Strip Modifications Herbicide and Mash









PSTA Cell Monitoring Well Locations



PSTA Cell Monitoring Well Sampling





Proposed HW and TW Sensors

- Sensors at G-378E HW and G-379E TW are needed because sensors at nearby "surrogate" structures are currently being used to estimate flow
- Differences in surface water elevation in treatment cells upstream and downstream of these structures as compared to the surrogates cause large errors in flow estimates <u>and TP measurements</u>
- Accuracy of water and phosphorus budgets for the overall PSTA project has been impacted, and as a result, confidence in the data associated with the PSTA project is not as good as it could be if more accurate flow data were available



Proposed HW Sensor at G-378E





Proposed TW Sensor at G-379E





PSTA Research Plan



Transect Row & Column

Α

В

С

D

Е

F

G

Η

J

K

Μ



PSTA Inflow (G-390A sampled only if flowing)

PSTA Research Plan Sampling locations

PSTA Cell Internal Sampling Locations

Surface Water

TP, TSP, SRP, DOC, UV absorbance, alkaline

• phosphatase activity (APA), calcium, sulfate, NH_4 -N, NOx, TKN,

- TP, TSP, SRP, DOC, UV absorbance Total P only
 - Remote P analyzer

Vegetation and Sediment

Monitoring for semi-quantitative SAV cover & floc depth



Sediment, SAV and periphyton chemistry, SAV biomass, periphyton APA

Periphytometer deployment

Hydraulic and hydrology

- O Internal stage recorder
- Seepage water level
- Seepage water quality

Draft Date: 4/24/2012

PSTA Outflow



Questions?

STA-3/4 Periphyton-Based Stormwater Treatment Area Project Update

Tracey Piccone, P.E., Chief Consulting Engineer Water Quality Treatment Technologies Section

