

Restoration Strategies Science Plan

# Use of Soil Amendments/Management to Control P Flux

Quarterly Long-term Plan Meeting  
December 3, 2015

**Michael Chimney, Ph.D.**

Lead Scientist  
Applied Sciences Bureau

# Study Hypothesis

- Reducing the flux of phosphorus (P) from the soil to the water column in an operating STA will lead to a reduction of P concentration in surface water at the outflow

# Key Study Question

- How can internal loading of phosphorus to the water column be reduced or controlled, especially in the lower reaches of the treatment trains?

# Original Study Design

- Conducted in three phases with a **STOP-GO** decision to proceed after Phases I and II
- **Phase I**
  - Expand preliminary literature review
  - Summarize relevant past SFWMD studies
  - Conduct a feasibility assessment to the extent practicable
- **Phase II**
  - Conduct small-scale short-term screening experiments based on Phase I results
- **Phase III**
  - Conduct large-scale long-term field trials based on Phase II results, need this scale for obtain design information

# Study Components

- Soil Amendments
  - Natural minerals, manufactured materials, waste by-products [adsorption/precipitation]
  - ~~Wood chips~~ [carbon source]
- Soil Management Techniques
  - Soil inversion
  - Soil capping
  - ~~Soil removal~~

# Draft Phase I Report

- Literature review – soil amendments
  - 100+ materials identified
  - Many inorganic materials containing Al, Fe, Ca or Mg will sequester P to some degree
  - Cannot cross-compare different studies due to differences in study methodology & conditions
  - Most studies were short-term, small-scale and tested high P wastewater or farm runoff
  - The few long-term data available demonstrate that soil amendments become saturated over time and lose effectiveness to remove P

# Draft Phase I Report (cont.)

- Literature review – soil management
  - Soil capping [reactive materials (e.g., alum)] and soil removal are used in lake management
  - SJRWMD wetland soil capping demo (Hoge et al., 2003) – 2-ac cells
  - Soil inversion and soil removal proposed for nutrient management in agricultural systems & treatment wetlands, respectively

# Draft Phase I Report (cont.)

- Relevant District studies
  - Chimney et al. (2007) – soil cores/Reclime<sup>®</sup>
  - CH2M Hill (2003) - mesocosms
  - PSTA Field-scale cell (5 ac) – limerock cap
  - PSTA Field-scale cell (5 ac) – soil removal
  - STA-3/4 PSTA cell (100 ac) –soil removal
  - Soil inversion field-scale demonstrations for Cu & P remediation



# Draft Phase I Report (cont.)

- Feasibility assessment
  - **Constructability** – no foreseen problems
  - **Treatment Efficacy** – found no published case studies on long-term effectiveness of soil amendments/management in treatment wetlands; District studies small-scale, short-term and/or did not experience large storm pulses
  - **Operations & Regulatory Issues** – nothing foreseen that would prohibit using these technologies


# Draft Phase I Report (cont.)

- Feasibility assessment (cont.)
  - **Economics**
    - Costs were estimated for revised large-scale test facilities (infrastructure only) and full-scale implementation of technologies
    - Two new options for large-scale tests replaced the 10-ac cells originally proposed in the detailed study plan

# Large-scale Test Facilities

## Option #1 – STA Expansion Area

- Test of soil inversion
- All soil in Cell 7 will be inverted to mitigate Cu
- Use Cell 8 as a control, no soil inversion
- Expansion area will be flow-capable by Dec 31, 2018
- Test only require autosamplers, estimated infrastructure cost ~ \$177K




# Large-scale Test Facilities (cont.)

## Option #2 – Cells in existing STAs

- Partition SAV cells in STA-1E, 1W, 3/4 and 5/6
- Parallel sub-cells range in size from 48 to 612 ac
- Test 1 soil amendment, soil capping, soil inversion and control sub-cell
- Use existing inflow & outflow culverts

STA	Cost
1E	\$14.3M
1W	\$3.7M
3/4	\$14.7M
5/6	\$24.8M
<b>Total</b>	<b>\$57.5M</b>



# Full-scale Implementation

- Assumed installation in all SAV-dominated areas ~ 31,000 ac
- Soil amendments will need reapplication
- Limerock cap may need periodic maintenance

Technology	Cost
Soil Amendment <sup>1</sup>	\$99.1M
Limerock Cap <sup>2</sup>	\$876.4M
Soil Inversion <sup>3</sup>	\$85.6M

1 – Cost of one application  
2 – No maintenance costs  
3 – One-time cost

# STOP/GO Decision

- RS Science Plan Management Team
  - Proceed with Option #1 – Planning & budgeting to begin ~ Jan 2018
  - Table consideration of Option #2 for now
- RS Steering Committee
  - Concurred with the RS-SPMT STOP/GO recommendation

# Link to Summary Report on SFWMD.gov

[http://www.sfwmd.gov/portal/pls/portal/portal\\_apps.repository.lib\\_pkg.repository\\_browse?p\\_keywords=rsspoth&p\\_thumbnails=no](http://www.sfwmd.gov/portal/pls/portal/portal_apps.repository.lib_pkg.repository_browse?p_keywords=rsspoth&p_thumbnails=no)

TECHNICAL PUBLICATION  
WR-2015-006

Restoration Strategies Regional Water Quality Plan –  
Science Plan for the Everglades Stormwater Treatment Areas:

*Soil Amendments/Management to Control P Flux*

## Phase I Summary Report for the Use of Soil Amendments/Management to Control P Flux Study

Prepared by:  
Michael J. Chimney Ph.D.

Water Quality Treatment Technologies Section  
Applied Sciences Bureau, Water Resources Division  
South Florida Water Management District  
3301 Gun Club Road, West Palm Beach, FL 33406

October 2015



[sfwmd.gov](http://www.sfwmd.gov)