

# Tamiami Trail Flow Formula (TTFF) - Target Flow from WCA-3A to ENP

Daily Target Flow for	3/19/2024	to	3/25/2024	MAX	cfs
-----------------------	-----------	----	-----------	-----	-----

## Observed Stage Data

Station	Variable	on	3/15/2024	Value	Unit
WCA-3A (Average for Site 63, 64 and 65)	Average Daily Stage			10.26	ft-NGVD29
NESRS2	Average Daily Stage			7.97	ft-NGVD29
Regulatory Stage WCA-3A	Average Daily Stage			10.01	ft-NGVD29

## Observed Flow Data

Station	Variable	From	3/9/2024	to	3/15/2024	Value	Unit
S-12A	7-day Average Daily Flow					210	cfs
S-12B	7-day Average Daily Flow					172	cfs
S-12C	7-day Average Daily Flow					430	cfs
S-12D	7-day Average Daily Flow					654	cfs
S-333	7-day Average Daily Flow					184	cfs
S-333N	7-day Average Daily Flow					178	cfs
S-334	7-day Average Daily Flow					0	cfs
S-12s Total	7-day Average Daily Flow					1466	cfs
S333 + S333N - S334 <sup>1</sup>	7-day Average Daily Flow					362	cfs
Total Flow to ENP	7-day Average Daily Flow					1828	cfs

## Meteorological Data

Forecasted	From	3/16/2024	to	3/22/2024	Value	Unit
WCA3 7-day Quantitative Precipitation Forecast (QPF)					0.07	in
3AS3WX - 7-day Total Forecasted PET					1.08	in
Observed	From	3/9/2024	to	3/15/2024	Value	Unit
WCA-3 7-day Total Observed NEXRAD Rainfall					0.01	in
3AS3WX 7-day Total Observed PET					1.08	in

TTFF Application				
1	Previous week target flow (calculated with forecasted 7-day QPF and PET)			MAX cfs
2	Previous week target flow (recalculated with observed rainfall and PET)			MAX cfs
3	Adjustment for forecast (2-1)			0 cfs
4	This week calculated target flow			MAX cfs
5	This week target flow with adjustment (3 + 4)			MAX cfs
Average Daily Target Flow <sup>2</sup>				MAX cfs

TTFF formula coefficients					
WCA-3A Average Stage (β1)	NESRS2 Stage (β2)	Previous 7-day Average Flow (β3)	Forecast Precipitation (β4)	Forecast PET (β5)	Regulation Schedule Stage (β6)
318.42	-44.62	0.644	24.32	-96.31	-221.79

Target flow is distributed from east to west (S-333, S-12D, S-12C, S-12B, and S-12A) to prioritize water deliveries to NESRS first and WSRS second, subject to downstream constraints.

<sup>1</sup>S-333 + S-333N - S-334 becomes zero if the sum of S-333 and S-333N is less than S-334 flow. Calculation is done daily.

<sup>2</sup>Actual discharges may vary from target discharges because of changing hydrologic conditions.

