

M E M O R A N D U M

TO: Jeff Kivett, Director, Operations, Engineering & Construction Division
Terrie Bates, Director, Water Resources Division

FROM: Akin Owosina, Chief, Hydraulics & Hydrology Bureau
John Mitnik, Chief, Engineering & Construction Bureau
Susan Gray, Chief, Applied Science Bureau
Dean Powell, Chief, Water Supply Bureau

DATE: September 3, 2015

SUBJECT: Operational Position Statement for September 1 – September 7, 2015

The U.S. Army Corps of Engineers (USACE) is responsible for managing Lake Okeechobee water levels and makes operational decisions about whether to retain water or release water based on their regulation schedule release guidance (2008 LORS). The USACE makes this decision taking into account the best available science and data provided by its staff and a variety of partners, which includes the South Florida Water Management District (SFWMD).

The SFWMD team has discussed the system-wide environmental conditions, the water supply conditions, and has evaluated the overall status of the water management system. Detailed reports are available at the SFWMD Operational Planning internet page.

This Position Statement is for the period from September 1 through September 7, 2015. At the time of this recommendation, the Lake Okeechobee stage is in the Base Flow Sub-band. Correspondingly Part C and Part D of the 2008 LORS recommend regulatory releases to the WCAs and Base Flow releases to the estuaries to manage lake stages. The SFWMD recommendation is to follow the Lake Okeechobee Adaptive Protocols (AP) release guidance which calls for no lake releases at S-77 because the Caloosahatchee Estuary does not “need” freshwater per the salinity criterion. Specifically, the 30-day average salinity is expected not to raise above the 5 practical salinity units (psu) at the Val-I75 site within the next two weeks.

The SFWMD governing board directed staff to use the SFWMD’s Lake Okeechobee Adaptive Protocols (AP) release guidance as the basis for S-77 release recommendations to the USACE when the lake stage is within or below the Base Flow Sub-band.

The SFWMD recognizes the wet season continues and the USACE may need to manage rising Lake Okeechobee stages by making Base Flow releases. If releases are needed in the future and C-43 basin runoff decreases sufficiently, the SFWMD recommends that the USACE use a pulse release, which is less harmful. Suggested daily discharge rates for 7-day pulses are provided in Table 1 at the end of this memorandum.

The most recent Climate Prediction Center (CPC) outlook for Central and South Florida indicates equal chances (EC) of below, normal and above-normal precipitation for the month of September and the three-month window September to November. The CPC rainfall outlook for the 2015-2016 dry season predicts a substantial increase in the likelihood for above-normal precipitation. SFWMD rainfall for the month of August was above average. Rainfall for the next week is forecast to be above average, while the second week forecast is in between below-average and average conditions.

Over the 7-day period from August 25 to August 31, 2015, there were no deliveries from Lake Okeechobee to the STAs.

2008 LORS Release Guidance (Part C): The Lake Okeechobee stage is currently within the Base Flow Sub-band and Part C of the 2008 LORS release guidance recommends “Up to Maximum Practicable to the WCAs if desirable or with minimum Everglades Impacts”.

Consistent with the LORS release guidance, the USACE is requesting the SFWMD to implement maximum practicable Lake Okeechobee regulatory releases to the WCAs. However, current and expected conditions will substantially limit capacity for releases south. After above average rainfall for the last 7 days, canals and STAs are still treating runoff from the EAA and current stages mostly exceed target stages for optimal vegetation growth. In addition, newly starting crop operations in the EAA will require additional drainage and will use canal capacity. The District will continue to monitor the situation for opportunities to send releases south. If this becomes feasible, releases should be sent to STA-1E and STA-2.

District Everglades scientists have indicated that additional releases south would be beneficial or with minimum impact to the WCAs. Release from STA-1E into WCA-1 will help maintain ascension rates and help in moving water down the system to the other WCAs. Releases from STA-2 into WCA-2 could be delivered to WCA-3A through the S-11 structures, which are currently open. North east WCA-3A remains dry and additional releases through S-150 will help protect peat and wetlands until water levels get above ground.

2008 LORS Release Guidance (Part D): The Lake Okeechobee stage is currently within the Base Flow Sub-band and Part C of the 2008 LORS release guidance is “S-79 up to 450 cfs and S-80 up to 200 cfs”

No regulatory releases from Lake Okeechobee to the St. Lucie and Caloosahatchee Estuaries have occurred since 29-May and 12-June, respectively. Over the past week, flows in the amount of 342 cfs entered the St. Lucie Estuary through S-80, with no contributions from the lake. Flow at S-79 averaged approximately 2,900 cfs with no releases from the lake through S-77.

SFWMD lake scientists report that from an ecological point of view the current stage ascension rate is steep and above the recommended value, but that at the same time the lake stage is still below optimal for this time of the year. As far as possible, a steady increase in stage not to exceed 0.5 feet per month throughout the wet season is recommended.

Currently, there are no ecological benefits associated with additional releases from Lake Okeechobee to the estuaries. In the St. Lucie Estuary, salinity was in the good range for adult oysters. In the Caloosahatchee Estuary, salinity continued to be in the good range for adult oysters at Shell Point and Sanibel, but remained in the poor range at Cape Coral due to relatively high basin runoff. Salinities were also in the good range for tape grass in the upper-Caloosahatchee Estuary, and are forecasted to remain so over the next two weeks, even with no flow through S-79.

In contrast to the more northern estuaries, conditions in Florida Bay continue to be hypersaline with salinities 5 to 30 psu above average for this time of year, with the lowest salinity at 38.8 psu. The cause is below average rainfall for the Everglades and the southern portion of the District, high evaporation, and lack of freshwater inflows into the Bay. No operational actions are possible at this point in time to reverse these conditions. Transition to a more typical wet season rainfall in south Florida will improve these conditions.

SFWMD Lake Okeechobee Adaptive Protocol (AP) Release Guidance

This week the SFWMD’s Lake Okeechobee Adaptive Protocol (AP) release guidance flowchart is applicable since the Lake Okeechobee stage is within the Base Flow Sub-band of the 2008

LORS. The Adaptive Protocols process is documented in the District publication Final Adaptive Protocols for Lake Okeechobee Operations (September 16th, 2010).

This week the Lake Okeechobee AP release guidance suggests no releases from Lake Okeechobee at S-77. This week's outcome is based on the current and forecast salinity at the Val-I75 site being below the 5 psu threshold. The specific salinity criterion in the AP release guidance states "Estuary 'needs' water when the 30-day moving average salinity at I-75 bridge is projected to exceed 5 psu within 2 weeks." If the dry conditions continue and the 14-day salinity forecast shows the 30-day moving average staying below 5 psu, then the AP guidance will continue to suggest no releases at S-77.

For additional information pertaining to operations history and past recommendations, refer to the archives of LORS-2008 Release Guidance outcomes and operational position statements at www.sfwmd.gov under the Operational Planning topic.

Table 1. Schedules for 7-day pulses at S-80 and S-79

7-day Pulse Release at S-80

Day	100 cfs	200 cfs
1	100	200
2	300	600
3	150	300
4	100	200
5	50	100
6	0	0
7	0	0

7-day Pulse Release at S-79

Day	100 cfs	450 cfs	650 cfs
1	100	450	650
2	300	850	1100
3	150	700	900
4	100	550	800
5	50	350	600
6	0	250	400
7	0	0	100